LYNN PEAVEY COMPANY

SECTION 4 —FIRE AND EXPROSION DATA FLASH POINT not determined EXTINGUISHING MEDIA suitable dry chemical UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	MATERIAL SAFETY DATA SHEET						
Name ODV, Inc. Address P.O. Box 180, 9 Swallow Road, S. Paris, ME 0422 Section For Additional Information Contact: Larry Down Not Apply		0	M 13150001		69	{ (
Name ODV, Inc. Address P.O. Box 180, 9 Swallow Road, S. Parls, ME 0428 Telephone Number 207-743-7712 For Additional Information Contact: Larry Dow February 1, 2002 Common name (used on Label) 922 or 7822 Opiates Reagent Trade name & Synonyms NarcoPouch* & Narcotest* Chemical Family Does Not Apply Chemical Name Does Not Apply SECTION 2 HAZARDOUS INGREDIENTS HAZARDOUS COMPONENT CAS # % (wt) TLV PEL Sulfuric Acid concentrated Ammonium Molybdate 13106-76-8 9.5 1 mg/m² 5 mg/m	one a rozz opiatoo ricagoni	P.O. BOX 180 TEL: 207-743					
Telephone Number 207-743-7712 For Additional Information Contact: Date Prepared February 1, 2002 Common name (used on Label) 922 or 7622 Opiates Reagent Trade name & Synonyms NarcoPouch* & Narcotest* Does Not Apply Does Not Apply Formula Does		C. Bartone Statement Company of the	ION 1 ADEN	TITY!			
Common name (used on Label) 922 or 7622 Opiates Reagent Trade name & Synonyms NarcoPouch* & Narcotest* Chemical Family Does Not Apply Does Not Apply SECTION 2 HAZARDOUS INGREDIENTS HAZARDOUS COMPONENT CAS # % (wt) TLV PEL Sulfuric Acid concentrated Ammonium Molybdate 7684-93-9 93 1 mg/m²/10 hr. 1 mg/m² 5 mg/m² Ammonium Molybdate 7684-93-9 9.5 1 mg/m²/10 hr. 5 mg/m² TV: Threshold limit Value established by the Occupational Safety and Health Administration TV: Threshold limit Value established by the American Conference of Governmental Industrial Hygienists, 1987-88. SECTION 3 PHYSICAL DATA SPECIFIC GRAVITY (H, O = 1) Low PRESSURE (mm Hg) Low Low PRESSURE (mm Hg) Low Low PRESSURE (mm Hg) Low	Name ODV, Inc.		Address	P.O. Box	180, 9 Swallow Road	, S. Paris, ME 04281	
Chemical Name Does Not Apply Formula Does Not Apply Formula Does Not Apply Formula Does Not Apply SECTION 2 HAZARDOUS-INGREDIENTS HAZARDOUS COMPONENT CAS # % (wt) TLV PEL Sulfuric Acid concentrated Ammonium Molybdate 7684-93-9 13106-76-8 9.5 13106-76-8 9.5 1 mg/m³/10 hr. 1 mg/m³ 5 mg/m³ 5 mg/m³ Ttv: Threshold limit Value established by the Occupational Safety and Health Administration Ttv: Threshold limit Value established by the American Conference of Governmental Industrial Hygienists, 1987-88. SECTION 3 PHYSICALDATO SPECIFIC GRAVITY (H, O = 1) Low PERCENT VOLATILE BY VOLUME Not determined VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER Complete REACTIVITY IN WATER Complete REACTIVITY IN WATER Complete REACTIVITY IN WATER SECTION 4 FIRE AND EXPLOSION DATA FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% By Volume) LOWER: not determined UPPER: not determined LOWER: not determined UPPER: not determined LOWER: not determined UPPER: not determined	207-743-7712	v					
Chemical Name Does Not Apply Formula Does Not Apply SECTION 2 HAZARDOUS-INGREDIENTS HAZARDOUS COMPONENT CAS # % (wt) TLV PEL Sulfuric Acid concentrated Ammonium Molybdate 7684-93-9 13106-76-8 0.5 1 mg/m² 5 mg/m² 5 mg/m² 5 mg/m² 5 mg/m² PEL: Permissible Exposure Limit established by the Occupational Safety and Health Administration TLV: Threshold limit Value established by the American Conference of Governmental Industrial Hygienists, 1987-88. SECTION 3 FHYSICAL DATA SPECIFIC GRAVITY (H, O = 1) Low VAPOR PRESSURE (mm Hg) Low PERCENT VOLATILE BY VOLUME not determined VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER Complete REACTIVITY IN WATER Reacts violently when water is added with evolution of heat. SECTION 4 FIRE AND EXPLOSION DATA FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% BY Volume) LOWER; not determined UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat. UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with	Common name (used on Label) 922 or 7622 Opiates Reagent						
Does Not Apply Does Not Apply	The state of the s			de 1660 - 1860000			
HAZARDOUS COMPONENT CAS # % (wt) TLV PEL Sulfuric Acid concentrated Ammonium Molybdate 7694-93-9 13106-76-8 99 13106-76-8 13106-76-							
Sulfuric Acid concentrated Ammonium Molybdate 7684-93-9 13106-76-8 0.5 1 mg/m³/10 hr. 1 mg/m³ 5 mg/m³ 5 mg/m³ 5 mg/m³ 13106-76-8 0.5 1 mg/m³/10 hr. 1 mg/m³ 5 mg/m³ 5 mg/m³ 5 mg/m³ 5 mg/m³ 5 mg/m³ 6 mg/m³ 5 mg/m³ 6							
Ammonium Molybdate 13106-76-8 0.5 5 mg/m¹ 5 mg/m¹ 13106-76-8 0.5 5 mg/m² 5 m	HAZARDOUS COMPONENT		CAS#	% (wt)	TLV	PEL	
SECTION 3 PHYSICAL DATA BOILING POINT not determined SPECIFIC GRAVITY (H,O = 1) Low							
PERCENT VOLATILE BY VOLUME not determined VAPOR DENSITY (AIR = 1) 3.40 PERCENT VOLATILE BY VOLUME not determined SOLUBILITY IN WATER Complete REACTIVITY IN WATER REACTIVITY IN WATER REACTIVITY IN WATER Reacts violently when water is added with evolution of heat. SECTION 4 FIRE AND EXPLOSION DATA FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% By Volume) LOWER: not determined EXTINGUISHING MEDIA suitable dry chemical UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	TLV: Threshold limit Value established by the American Conference of Governmental Industrial Hygienists, 1987-88.						
SOLUBILITY IN WATER Complete REACTIVITY IN WATER Reacts violently when water is added with evolution of heat. APPEARANCE AND ODOR Clear liquid and Odorless SECTIONA—FIRE AND EXPEOSION DATA FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% By Volume) LOWER: not determined UPPER: not determined EXTINGUISHING MEDIA suitable dry chemical UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	BOILING POINT not determined					(mm Hg)	
APPEARANCE AND ODOR Clear liquid and Odorless SECTION 4—FIRE AND EXPLOSION DATA FLASH POINT not determined FLASH POINT not determined EXTINGUISHING MEDIA suitable dry chemical UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	PERCENT VOLATILE BY VOLUME not determined VA	AIR = 1) 3.40					
SECTION 4—FIRE AND EXPLOSION DATA FLASH POINT not determined EXTINGUISHING MEDIA suitable dry chemical UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with	SOLUBILITY IN WATER Complete	REACTIVITY IN	REACTIVITY IN WATER Reacts violently when water is added with				
FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% By Volume) LOWER: not determined UPPER: not determined EXTINGUISHING MEDIA suitable dry chemical AUTO IGNITION TEMPERATURE not determined UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	ADDITADANCE AND ODOD						
FLASH POINT not determined FLAMMABLE LIMITS IN AIR (% By Volume) LOWER: not determined UPPER: not determined EXTINGUISHING MEDIA suitable dry chemical AUTO IGNITION TEMPERATURE not determined UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.							
EXTINGUISHING MEDIA suitable dry chemical AUTO IGNITION TEMPERATURE not determined UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	SECTION 4 FIRE AND EXPENSION DATA						
UNUSUAL FIRE AND EXPLOSION HAZARDS Reacts violently when water is added or with organic materials with evolution of heat.	not determined	LOWE	LOWER: not determined UPPER: not determined				
evolution of heat.				l			
CDECIAL FIRE FIGURING PROCEDURES. Denoting water to put out for Met.	UNUSUAL FIRE AND EXPLOSION HAZARDS 6	Reacts violently evolution of heat	when water is added	d or with organ	nic materials with		
CDECIAL FIRE SIGNATURE PROCEDURES. Do not use water to put out #1. Mid-							
SPECIAL FIRE FIGHTING PROCEDURES Do not use water to put out fire if the water can get into concentrated sulfuric acid. Use proper respiratory protection against fumes.	SPECIAL FIRE FIGHTING PROCEDURES Do sui	not use water to furic acid. Use p	o put out fire if the w proper respiratory pr	ater can get in otection again	nto concentrated nst fumes.		

SECTION OF HEALTH-INFORMATION - SECTION
PRIMARY ROUTES OF EXPOSURE Inhalation, contact with eyes or skin.
SIGNS AND SYMPTOMS OF EXPOSURE _ Irritation of eyes, nose and throat. Splashes in the eyes or on the skin will cause severe skin burns.
(2) CHRONIC OVEREXPOSURE _ Repeated or prolonged exposure to dilute solutions of sulfuric acid may cause irritation of the skin. Repeated or prolonged exposure to mists or vapors of sulfuric acid may cause erosion of teeth,
chronic irritation of the eyes, or chronic inflammation of the nose, throat, and bronchial tubes.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Impaired pulmonary function, pre-existing eye problems, pre-existing skin disorders.
CHEMICAL/COMPONENT LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN NTP IARC OSHA None. IARC OSHA
OTHER EXPOSURE LIMITS None.
EMERGENCY & FIRST AID PROCEDURES In the case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes
while removing contaminated clothing and shoes. Call a physician. If swallowed, do not give emetics. If conscious, give tap water, milk, or milk of magnesia. Call a physician.
SECTION'S - REACTIVITY DATA
STABILITY Unstable Stable Stable CONDITIONS TO AVOID Avoid adding water to the acid, large amounts of heat is produced.
INCOMPATIBILITY (MATERIALS TO AVOID) Avoid contact of acid with organic materials (such as chlorates, carbides, fulminates, and picrates) may
cause fires and explosions. Contact of acid with metals may form toxic sulfur dioxide fumes and flammable hydrogen gas.
HAZARDOUS DECOMPOSITION PRODUCTS Heat, sulfur dioxide, hydrogen, ammonia
HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID May occur Will not occur X Not applicable to polymerization.
SECTION 7 - SPILL OR LEAK PROCEDURES.
STEPS TO BE TAKEN IN CASE MATERIAL IS LEAKED OR SPILLED Avoid adding water to the acid, large amounts of heat is produced.
WASTE DISPOSAL METHOD Dispose of wastes in accordance with Federal, State and Local codes. Normal disposal includes
neutralization and absorption in vermiculite, dry sand, earth, or similar material.
SECTION 8 PERSONAL PROTECTION INFORMATION
RESPIRATORY PROTECTION Respiratory protection is not required under normal and intended uses, Self-contained breathing apparatus required during fire fighting and spill clean-up.
VENTILATION Room ventilation is expected to be adequate except during spills or fires.
PROTECTIVE GLOVES Required when contact with sulfuric acid exists. EYE PROTECTION Required when possibility of contact with sulfuric acid exists.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT An eye wash fountain and safety shower should be readily available where contact with sulfuric acid exists.
SECTION 9 SPECIAL PRECAUTIONS -
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store and handle according to packaged instructions. Store in a cool well ventilated area. Keep away from reactive materials.
OTHER PRECAUTIONS Do not get in eyes, on skin, or on clothing. Avoid breathing vapor. Wash thoroughly after handling. Be prepared to neutralize.
The above information is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. ODV, inc. shall not be held liable for any damage resulting from handling or from contact with the above product.